



Thinking of you
Electrolux

Electrolux Professional Line 5000

Electrolux Super "S" Washers 200 G-force for OPL

Electrolux smart washers will forever change the way you do laundry

Imagine a washer smart enough to weigh the load size and add precisely the correct amount of water. Imagine a laundry chemical controller smart enough to adjust dosing for accurate water ratio each time.

Electrolux Professional washers do all that and more! An estimated 60-70% of washers are underloaded, wasting water, chemicals, and energy. That's why Electrolux developed Automatic Water Savings (AWS), a unique feature that automatically matches water consumption to load size. Combine that with SmartDosing which adjusts laundry chemicals to water ratio, and you will see immediate savings and superior wash results – every time, automatically.

Features and Benefits:

Electrolux Professional 200 G-Force high-speed extraction washers minimize drying time and provide significant electrical and gas savings. On-premises laundries benefit from higher productivity and lower costs. On-premises laundries can go right to flatwork finishing equipment after conditioning items in the dryer. You'll get superior results while saving valuable time and money.

- Save up to 30% on water with AWS, automatically
- Smart Dosing automatically adjusts the ratio of laundry chemicals to water resulting in lower costs and a superior wash.
- Convenient 4-compartment supply dispenser
- Provisions to connect up to 5 liquid supplies
- USB in front for easy access and programming
- Single phase 120 or 220 volt electrical service reduces installation costs
- Heavy-duty construction with robust steel door and lock, hinges wide apart
- Stainless and galvanized steel in all vital parts for maximum rust protection
- Super Balance guarantees the correct extraction force, longer machine life
- External liquid manifold improves reliability, workflow

Compass Pro microprocessor offers:

- Up to 55 programs, 15 custom
- Large display and one control knob for easy program selection
- More than 20 languages available
- Smart Start - real time clock for delayed start
- Detailed user statistics and programmability



Available in 20, 25, 30, 45, 62 & 77 lb. capacities. Vertical blue wave front panel standard. Stainless available. Most sizes available in 220 or 120 volt, single phase.

Electrolux models are designed to save water and energy and achieve impressive Modified Energy Factor (MEF) results.



Designed by experts. Inspired by you.

For more information, please visit www.laundrylux.com

fits through 36" door!

Electrolux S-Series Models	W585S		W5105S		W5130S		W5180S		W5250S		W5330S	
Capacity (lb/kg)	20	9	25	11	30	14	45	20	62	28	77	35
Width (in/mm)	26	660	28 3/8	720	28 3/8	720	29 1/2	750	32 11/16	830	35 13/16	910
Depth (overall) (in/mm)	30 1/8	765	29 1/8	740	32 1/2	825	36	915	39	990	42 5/16	1075
Height (in/mm)	43 7/8	1115	47 1/4	1200	47 1/4	1200	52 3/16	1325	55 1/2	1410	56 7/8	1445
Height to bottom of door (in/mm)	14	355	14 3/8	365	14 3/8	365	17 1/8	435	18 1/2	470	19 11/16	500
Door opening diameter (in/mm)	12 3/16	310	14 3/8	365	15 9/16	395	15 9/16	395	17 1/8	435	17 1/8	435
Cylinder volume (ft ³ /l)	3	85	3.7	105	4.6	130	6.4	180	8.8	250	11.7	330
Cylinder diameter (in/mm)	20 1/2	520	23 7/16	595	23 7/16	595	25 9/16	650	28 9/16	725	31 5/16	795
Drain outlet diameter (in/mm)	3	75	3	75	3	75	3	75	3	75	3	75
Height to centerline of drain (in/mm)	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100
Height to electrical connection (in/mm)	32 1/2	825	35 13/16	910	35 13/16	910	40 3/4	1035	44 1/8	1120	45 1/2	1155
Height to water connections (in/mm) (approx)	40 9/16	1030	43 7/8	1115	43 7/8	1115	49	1245	52 3/8	1330	53 3/4	1365
Dynamic load (lb/kN)	382+/-742	1.7+/-3.3	472+/-899	2.1+/-4.0	517+/-1057	2.3+/-4.7	2.3+/-4.7	2.7+/-5.9	832+/-1664	3.7+/-7.4	994+/-1978	4.2+/-8.8
Dynamic frequency (Hz)	11.6		10.8		10.8		10.3		9.8		9.4	
Noise level (dBA)	66		71		71		76		79		77	
Net wt (lb/kg)	298	135	385	175	386	175	503	228	633	287	675	306
Crated weight (lb/kg)	344	156	431	196	432	196	529	240	666	302	719	328
Operating Speeds												
Wash (rpm)	52		46		46		44		42		40	
Extract (rpm/G-Force)	830 / 220		776 / 200		776 / 200		742 / 200		702 / 200		641 / 200	
Electrical Requirements (standard)												
Voltage/frequency/phase	208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1-3 phase		208-240/60/1-3 phase	
Full-load current (Amps) / Ckt breaker (Amps)	3.5 / 15		3.8/15		3.8 / 15		5/15		6.9 / 15		9/15	
Voltage/frequency/phase	120/60/1		120/60/1		120/60/1		120/60/1		120/60/1		-	
Full-load current (Amps) / Ckt breaker (Amps)	7/15		7.6 / 15		7.6 / 15		9.5 / 15		13.2 / 20		-	
Water Information												
Inlet fittings (* = 3 inlets)	3/4	DN20	3/4	DN20	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
Flow (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	5	20	5	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	150-400	30-90	150-400	30-90	150-400	30-90	150-400

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.



Electrolux Professional Line 5000 The all-in-one business solution for your on-premises laundry.



Smart Dosing provides unmatched efficiency and economy

- System automatically calculates correct amount of detergent
- More efficient, better results
- Cuts chemical costs



External liquid chemical manifold - Best design in the industry

- Chemicals are diluted in water reservoir
- Improves reliability, operation, workflow
- Reduces maintenance



Cost savings in water and energy with Automatic Water Savings (AWS)

- Determines load weight and adds precisely the correct amount of water
- Up to 30% water savings - automatically
- Less water to heat
- Reduces water and energy consumption



For Electrolux Professional Laundry Solutions in North America:

Laundrylux

800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010

Please contact your local authorized Electrolux Professional Distributor.

HK Laundry Equipment, Inc

530 Main Street

Armonk, NY. 10504

800-229-4572

www.hklaundry.com



**ELECTROLUX
AUTHORIZED
PARTNER**