



Thinking of you
Electrolux

Electrolux Professional Line 5000

Electrolux 100 G-force Washers N-Series, Normal Spin for OPL

Electrolux washers feature Compass Pro, low water consumption, and robust design

Electrolux Professional 100 G-Force extraction normal spin washers combine world-class reliability with innovative features and programmability.

Electrolux washers increase your productivity, lower utility costs, and provide significant electrical and gas savings. With innovative design and high performance features, Electrolux washers come standard with Compass Pro for easy customization and flexibility.

- Low water consumption
- Single phase 220 volt electrical service reduces installation costs
- Convenient 4-compartment supply dispenser lets you conveniently add all laundry supplies before starting the wash
- Provisions to connect up to 5 liquid supplies
- USB in front for easy access and programming
- Door unlocks immediately at the end of final cycle. No delays.
- Heavy-duty construction with robust steel door and lock, hinges wide apart
- Stainless and galvanized steel in all vital parts for maximum rust protection
- Inverter driven motor for smooth and quiet operation, high efficiency
- External liquid manifold improves reliability, workflow, and operation. Best design in the industry. Chemicals are diluted in water reservoir. Reduces maintenance



Available in 30, 45, 62 & 77 lb. capacities.
Vertical blue wave front panel standard.
Stainless available. Most sizes available in
220 or 120 volt, single phase.

Electrolux models are designed to save
water and energy and achieve impressive
Modified Energy Factor (MEF) results.

Compass Pro microprocessor features and benefits

Compass Pro microprocessor provides the ultimate in flexibility and control over your laundry operations.

- Up to 55 programs, 15 custom
- Large display and one control knob for easy program selection
- Two languages displayed simultaneously
- Smart Start - real time clock for delayed start
- Detailed user statistics and programmability
- Reduce operator error by displaying only the programs you use.



Designed by experts. Inspired by you.

For more information, please visit www.laundrylux.com

Electrolux Professional Line 5000

The all-in-one business solution for your on-premises laundry.

Electrolux N-Series Models	W5130N		W5180N		W5250N		W5330N	
Capacity (lb/kg)	30	14	45	20	62	28	77	35
Width (in/mm)	28 3/8	720	29 1/2	750	32 11/16	830	35 13/16	910
Depth (overall) (in/mm)	32 1/2	825	36	915	39	990	42 5/16	1075
Height (in/mm)	47 1/4	1200	52 3/16	1325	55 1/2	1410	56 7/8	1445
Crated width - (in/mm)	29 1/2	750	30 11/16	780	33 7/8	860	37	940
Crated depth - (in/mm)	37 3/8	950	39 3/16	995	43 11/16	1110	47 1/16	1195
Crated height - (in/mm)	53 1/8	1350	56 7/16	1434	61 1/4	1556	62 7/16	1586
Height to bottom of door (in/mm)	14 3/8	365	17 1/8	435	18 1/2	470	19 11/16	500
Door opening diameter (in/mm)	15 9/16	395	15 9/16	395	17 1/8	435	17 1/8	435
Cylinder volume (ft3/l)	4.6	130	6.4	180	8.8	250	11.7	330
Cylinder diameter (in/mm)	23 7/16	595	25 9/16	650	28 9/16	725	31 5/16	795
Cylinder depth (in/mm)	18 7/16	468	21 5/16	542	23 7/8	606	26 3/16	665
Drain outlet diameter (in/mm)	3	75	3	75	3	75	3	75
Height to centerline of drain (in/mm)	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100
Height to electrical connection (in/mm)	35 13/16	910	40 3/4	1035	44 1/8	1120	45 1/2	1155
Height to water connections (in/mm) (approx)	43 7/8	1115	49	1245	52 3/8	1330	53 3/4	1365
Dynamic load (lb/kN)	518+/-912	2.3+/-4.1	611+/-1057	2.9+/-4.7	842+/-1189	3.7+/-5.3	1019+/-1310	4.5+/-5.8
Dynamic frequency (Hz)	8.7		8.4		7.9		7.5	
Noise level (dBA)	71		76		79		77	
Net wt (lb/kg)	385	175	502	228	631	287	656	298
Crated weight (lb/kg)	431	196	528	240	664	302	700	318
Operating Speeds								
Wash (rpm)	46		44		42		40	
Extract (rpm/G-Force)	548/100		525/100		497/100		474/100	
Electrical Requirements (standard)								
Voltage/frequency/phase	208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1	
Full-load current (Amps) / Ckt breaker (Amps)	3.8 / 15		5/15		6.9 / 15		9/15	
Voltage/frequency/phase	120/60/1		120/60/1		120/60/1		-	
Full-load current (Amps) / Ckt breaker (Amps)	7.6 / 15		9.5 / 15		13.2 / 20		-	
Water Information								
Inlet fittings (* = 3 inlets)	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
Flow (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600



ELECTROLUX
AUTHORIZED
PARTNER

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.



Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

Laundrylux

800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338
516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010

HK Laundry Equipment, Inc.

530 Main Street

Armonk, NY. 10504

800 - 229 - 4572

www.hklaundry.com