

EXSM Washers for OPL

Built to last, Wascomat's EXSM washers are designed for efficiency and superior wash results. Precision-engineering reduces downtime and improve machine reliability. The high G-force extraction cuts drying time resulting in lower utility costs and higher laundry room productivity.



Available in 65, 80, and 135 lb. capacities.

Features and Benefits:

- Heavy-duty construction for demanding applications.
- Efficient frequency-controlled motor reduces peak power demand by 50% for big energy savings.
- Optional steam injection for precise control of water temperature.
- Built-in connection for automatic liquid injector.
 - Compass Pro® provides 5 liquid chemical signals.
 - Clarus Control® provides 4 liquid chemical signals, expandable to 8 signals.
- Standard 4-compartment supply dispenser for liquid or powder supplies on 65 lb and 80 lb models.
- Optional 5-compartment supply dispenser for liquids or powders available on 135 lb washer.
- Built-in diagnostics and statistics.

Compass Pro®

- Customize wash programs to raise efficiencies and lower costs
- More than 20 languages available – display two simultaneously
- Reduce operator error by displaying only the programs you use
- Up to 55 programs available, ability to create 15 custom programs
- USB on front for easy programming
- Real-time clock for delayed start

Clarus Control®

- Fully programmable microprocessor.
- All wash parameters can be programmed and customized.
- Programming from keypad or download via memory card.

Environmentally responsible.

With more than a century of experience behind every machine, Wascomat's state-of-the-art products are engineered for quality, energy savings, and water efficiency. When you buy Wascomat, you are truly investing in the future of your business.

**220-300 G-force extraction
for speed, performance
and BIG savings.**

BEST IN THE INDUSTRY!

External Liquid Chemical Manifold
for improved reliability, maintenance
and flushing using built in water
reservoir to promote 24/7 diluted
chemicals in dispensing system
– prevents chemical damage
to machine.

Wascomat "EXSM" Series, 220-300G Washers	EXSM765		EXSM780		EXSM 7135	
Capacity (lb/kg)	65	29	80	36	135	62
Width (in/mm)	36 13/16	935	42 11/16	1085	47 1/16	1195
Depth (in/mm)	38 3/16	970	43 1/2	1105	54 1/8	1375
Height (in/mm)	57 5/16	1455	61 13/16	1570	65 3/4	1670
Door opening diameter (in/mm)	16 1/8	410	21 1/16	535	21 1/16	535
Cylinder volume (ft ³ /l)	9.9	280	12.4	350	21.2	600
Crated weight (lb/kg)	891	405	1287	585	1760	800
Operating Speeds						
Extract (rpm/G-Force)	805 / 300		650 / 220		630 / 220	
Electrical Requirements (standard)						
Voltage/frequency/phase	208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~	
Full-load current (Amps) / Ckt breaker (Amps)	7.2A (15A)		12.0A (15A)		5.9Z (15A)	
Water Information						
Inlet fittings (2 hot inlets, 1 cold inlet)	3/4	DN20	3/4	DN20	1	DN25
Flow (gpm/lpm @ 45 psi) total	16	60	16	60	29	110
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	200-600
Steam supply (w/heating option) (psi/kPa)	40-90	300-600	40-90	300-600	40-90	300-600
Steam inlet	1/2	DN15	1/2	DN15	3/4	DN20
Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.						

Call today for information on the full line of Wascomat Commercial Laundry Equipment and low-cost financing.



Laundrylux
800.645.2205 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

Sales & Administration: 516-371-4400 • F 516-371-4204 • sales@laundrylux.com
Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com
Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010

