



## COMMERCIAL FLATWORK FINISHERS



### QUALITY BY DESIGN

Our heated cylinder finishers are equipped with a frequency-controlled motor, suspended roll and Nomex ironing belts to deliver top-of-the-industry results.


### THE RIGHT SIZES

Huebsch® flatwork finishers are offered in finished widths of 55, 66, 79, 82, 102 and 126 meaning there's a size to fit the needs of any size laundry.

### EXCELLENT EFFICIENCY

Thick, polished steel cylinders maintain even heat and help make the finishers highly efficient. A totally enclosed cabinet also contributes to its energy efficiency.

### MICROPROCESSOR CONTROL



Huebsch's versatile microprocessor control enables you to store temperature and speed settings to ensure consistent, top quality results. Temperatures can be set up to 355 degrees, while there are multiple speed settings.

# FLATWORK FINISHER

Models	I10	FCU13X66	FCU13X82	FCU20X79	FCU20X102	FCU20X126
Roll Diameter - in (mm)	10 (254)	13 (320)	13 (320)	20 (502)	20 (502)	20 (502)
Finishing Width - in (mm)	55 (1400)	66 (1664)	82 (2080)	79 (2000)	102 (2600)	126 (3200)
Ironing Speed - ft/m (m/m)	7-13 (2-4)	3-20 (1-6)	3-20 (1-6)	5-26 (1.5-8)	5-26 (1.5-8)	5-26 (1.5-8)
Ironer Dimensions (working position)						
Width - in (mm)	70.875 (1800)	86.5 (2194)	102.75 (2610)	108.25 (2750)	132 (3350)	155.5 (3950)
Depth - in (mm)	16.5 (420)	30 (765)	30 (765)	41.5 (1052)	42.75 (1087)	42.75 (1087)
Height - in (mm)	39.63 (1005)	43.75 (1110)	43.75 (1110)	48.5 (1232)	48.5 (1232)	48.5 (1232)
Roll Motor - HP (kW)	0.29 (0.215)	0.24 (.18)	0.24 (.18)	0.50 (.37)	0.50 (.37)	0.50 (.37)
Roll Exhaust Motor - HP (kW)	N/A	0.17 (0.125)	0.17 (0.125)	0.34 (0.255)	0.34 (2 x 0.255)	0.34 (2 x 0.255)
Roll Exhaust Duct - in (mm)	2.17 (55)	6 (150)	6 (150)	6 (150)	6 (2 x 150)	6 (2 x 150)
Electric Heating						
E heat input power - HP (kW)	11.3 (8.4)	32.6 (24.3)	37.4 (27.9)	49.9 (37.2)	72.4 (54.0)	86.9 (64.8)
Electrical Requirements - Circuit Breaker	230/60/3 - 25	230/60/3 • 80	230/60/3 • 80			
Gas Heating						
Maximum Gas Input - Btu (kW)	N/A	85,303 (25)	102,364 (30)	122,837 (36)	177,431 (52)	225,201 (66)
Gas Inlet - in (mm)	N/A	3/4 (19)	3/4 (19)	3/4 (19)	3/4 (19)	3/4 (19)
Electrical Requirements - Circuit Breaker	N/A	120/60/1 • 15	120/60/1 • 15	230/60/3 • 15	230/60/3 • 15	230/60/3 • 15
Shipping Dimensions						
Height - in (mm)	45 1/4 (1150)	49.63 (1260)	49.63 (1260)	59 (1550)	59 (1550)	59 (1550)
Width - in (mm)	74 (1880)	86.25 (2190)	102.75 (2610)	113.5 (2885)	137.25 (3485)	160.75 (4085)
Depth - in (mm)	19.69 (500)	31.5 (800)	31.5 (800)	43 (1095)	43 (1095)	43 (1095)
Weight - lb (kg)	Electric 328 (149) Gas N/A	1069 (485) 1025 (465)	1235 (560) 1191 (540)	2833 (1285) 3120 (1415)	3483 (1580) 3549 (1610)	4034 (1830) 4299 (1950)
Net Weight - lb (kg)	Electric 287 (130) Gas N/A	959 (435) 904 (410)	1080 (490) 1025 (465)	2249 (1020) 2535 (1150)	2778 (1260) 2844 (1290)	3241 (1470) 3505 (1590)
Approvals	ETL	CSA	CSA	CSA	CSA	CSA

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

©Copyright 2018 Alliance Laundry Systems LLC

Alliance Laundry Systems LLC  
 Shepard Street  
 Ripon, WI 54971  
 1-800-553-5120  
 huebsch.com

AH18-0035

