

Huebsch is the answer.



**OPL
25-35 lb DryStar™ Tumble Dryers
and 30-45 lb TwinStar™
Stack Tumble Dryers**



 **Huebsch®**



Huebsch is the answer.

Anybody can sell you laundry equipment and discuss the merits of each nut and bolt. However, at Huebsch, our priority is answering your questions about how working with us will make your business easier to run and more profitable.

Customers have selected Huebsch products for their ease of use, supreme durability and because owning a Huebsch product brings a service and support network that's unmatched within the industry. For profitability, reliability and ease of use, Huebsch is the answer.

Staying a Load Ahead

How are Huebsch DryStar™ tumble dryers the answer to helping my operation stay on top of its laundry challenges?

Highly efficient.

Huebsch DryStar™ tumble dryers utilize an axial airflow process, which reduces energy consumption and produces some of the industry's fastest dry times. This innovative drying process directs all heated air through the load at the optimum time in the tumble process. Faster drying cycles reduce processing times and help your operation maximize throughput.



Extra capacity.

With today's large capacity washers, it's easy for there to become backups on the drying side. Huebsch DryStars™ are offered in 25, 30 and 35 lb models to alleviate this scenario. Even the 25 lb model boasts a spacious 7.7 cu. ft. cylinder for efficient drying of large loads, ultimately giving your operation the tools for maximum productivity.

Quality You Can Touch

Laundry equipment is a sizable investment, how do I know Huebsch products are up to the rough demands of my on-premises laundry?

Rugged doors.

Doors can expect to see their share of slamming, wear and tear and overall mistreatment. DryStar™ and TwinStar™ doors are made of stainless steel to resist chipping and incorporate durable latches and hinges, to stand up to years of wear and stay looking good. You will see, feel and hear the quality every time you open or close the door.

Rugged shells.

Huebsch electrostatically applies paint for superior bonding. A baking process then produces a hard exterior shell that's both durable and looks good.

Staying in control.

DryStar™ models can be configured with either the Galaxy control or Dual Digital control. The Galaxy control features 30 programmable cycles and three cycle types that allow for greater consistency in drying. Laundry managers will see savings on their energy and labor costs as well as extended linen life. With the Dual Digital control, operators can set drying time (0-60 minutes), cool down time (0-15 minutes) and temperature (high, medium, low, no heat). Additional user-friendly features include a one-touch cycle repeat, automatic anti-wrinkle extended tumble and time remaining display.



Galaxy Control



Dual Digital Control

Easy To Own

How do DryStar™ models make things easier on me as an owner?

Low maintenance.

Large lint compartments mean DryStars™ don't have to be emptied as often as other models. Huebsch's

TwinStar™ Stack Tumble Dryers feature a new twist latch that eliminates the need for a key, saving additional time. In addition, a heavy-duty belt delivers a long life to reduce maintenance time and costs.

Short on Time and Space?

My laundry needs more drying capacity, but lacks the room to add equipment. How can Huebsch meet my needs?

Stack up the drying power.

The Huebsch TwinStar45™ and TwinStar30™ stack tumble dryers deliver 90 and 60 lbs of capacity, respectively. Laundries get the benefit of having two tumble dryers in the space of one. Best of all, splitting wash loads between the two cylinders delivers faster drying results than putting the full load in a 50 or 75 lb radial airflow tumble dryer.

A perfect fit.

Not only do Huebsch TwinStars™ deliver superior capacity and performance, but they also fit through a standard 36" door, making them the perfect replacement units.

Unmatched Durability

Commercial laundry equipment is no small expense; I want peace of mind my equipment will last well into the future. What sets Huebsch apart from other brands in terms of reliability?

Not just standing behind our equipment, but standing beside you and your business.

Our **Made-In-America** product comes with an industry-leading bond. The entire machine receives Huebsch's standard three-year warranty.



In addition, Huebsch has more service representatives in the field than most brands have in their whole organization. Huebsch support is further bolstered

by an online component and a distribution network that assists customers with their laundry questions.

*Parts only, labor not included. See Huebsch Warranty Bond for specifics.



25-35 lb Tumble Dryers and 30-45 lb Stack Tumble Dryer Specifications

Models	HT025	HT030	HTT30	HT035	HTT45
Control Options	Micro-Display (OM), Dual Digital (QT)	Micro-Display (OM), Dual Digital (QT)	Dual Digital (QT)	Micro-Display (OM), Dual Digital (QT)	Dual Digital (QT)
Dry Weight Capacity - lb (kg)	25 (11.3)	30 (13.6)	2 x 30 (13.6)	35 (15.9)	2 x 45 (20.4)
Width - in (mm)	28" (711)	28" (711)	31 1/2" (800)	31 1/2" (800)	34 1/2" (876)
Depth - in (mm)	40 7/8" (1038)	46 7/8" (1191)	42 3/4" (1086)	46 7/8" (1191)	48 5/8" (1235)
Height - in (mm)	63 7/8" (1622)	63 7/8" (1622)	76 1/4" (1937)	63 7/8" (1622)	81 1/16" (2059)
Cylinder Depth - in (mm)	24" (610)	30" (762)	26" (660)	30" (762)	30" (762)
Cylinder Diameter - in (mm)	26 1/2" (673)	26 1/2" (673)	30" (762)	30" (762)	33" (838)
Cylinder Volume - cu. ft. (liters)	7.7 (217)	9.6 (271)	10.6 (301)	12.3 (347)	14.8 (421)
Door Opening Size - in (mm)	22 11/16" (576)	22 11/16" (576)	22 11/16" (576)	22 11/16" (576)	26 7/8" (683)
Airflow - cfm (liters/sec.)	50 Hz: 430 (203) 60 Hz: 500 (236)	50 Hz: 430 (203) 60 Hz: 500 (236)	50 Hz: 340 (160) 60 Hz: 400 (189)	50 Hz: 550 (260) 60 Hz: 650 (307)	50 Hz: 500 (236) 60 Hz: 600 (283)
Energy Data	Gas Models: 50 Hz: 64,000 Btu/hr (18.8 kW) 60 Hz: 64,000 Btu/hr (18.8 kW) Steam Models: At 100 psi (6.9 bar): 3.9 BHP 135,000 Btu/hr (39.6 kW) Electric Models: 12 kW	Gas Models: 50 Hz: 73,000 Btu/hr (21.4 kW) 60 Hz: 73,000 Btu/hr (21.4 kW) Steam Models: At 100 psi (6.9 bar): 3.9 BHP 135,000 Btu/hr (39.6 kW) Electric Models: 21 kW	Gas Models: 50 Hz: 73,000 Btu/hr (21.4 kW) per pkct 60 Hz: 73,000 Btu/hr (21.4 kW) per pkct Steam Models: At 100 psi (6.9 bar): 3.2 BHP 111,000 Btu/hr (32.5 kW) Electric Models: 21 kW	Gas Models: 50 Hz: 90,000 Btu/hr (26.4 kW) 60 Hz: 90,000 Btu/hr (26.4 kW) Steam Models: At 100 psi (6.9 bar): 3.8 BHP 166,000 Btu/hr (48.6 kW) Electric Models: 24 kW	Gas Models: 50 Hz: 87,000 Btu/hr (25.5 kW) per pkct 60 Hz: 95,000 Btu/hr (27.8 kW) per pkct Steam Models: N/A Electric Models: N/A
Electrical Specifications	Gas and Steam 100/200-220/60/1 200/60/1 120/208-240/60/1 208-240/60/1 200-208/240/60/3 380/60/3 460-480/60/3 100/200/50/1 200/50/1 230-240/50/1 200/50/3 230-240/50/3 380/400-415/50/3 Electric* 208/60/1 240/60/1 200/60/1 200-208/60/3 240/60/3 380/60/3 460-480/60/3 200/50/1 230-240/50/1 200/50/3 230-240/50/3 380/50/3 400-415/50/3	Amps: 11.0/5.8 N/A 12.0/6.7 N/A 3.2/3.2 1.5 1.6 12.1/7.5 N/A 7.5 2.9 3.5 1.5/1.6 108 94 108 62 54 33 27 105 95 60 55 33 31	Amps: 22.0/11.6 total N/A 16.0/8.0 total N/A 6.4/6.4 total 3.0 total 3.3 total 24.2/15.0 total N/A 15.0 total 5.8 total 7.0 total 3.0/3.2 total N/A N/A N/A 124 total 108 total 66 total 54 total N/A N/A 120 total 110 total 66 total 62 total	Amps: 11.0/5.8 N/A 12.0/6.7 N/A 3.2/3.2 1.5 1.6 12.1/7.5 N/A 7.5 2.9 3.5 1.5/1.6 122 107 122 71 62 38 31 119 108 65 62 38 35	Amps: N/A 11.2 total N/A 12.0 total 9.6/9.6 total N/A N/A N/A 11.2 total 10.8 N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A
Plumbing Connections - in	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: N/A
Shipping Dimensions	Width 30" (762) Depth 43" (1092) Height 69" (1753)	30" (762) 49" (1245) 69" (1753)	32 1/2" (825) 47" (1194) 81" (2057)	33" (838) 49" (1245) 69" (1753)	35 1/2" (902) 54" (1372) 85" (2159)
Net Weight - lb (kg)	299 (135)	331 (150)	544 (247)	361 (164)	673 (305)
Shipping Weight - lb (kg)	332 (151)	364 (165)	582 (264)	394 (179)	718 (326)
Agency Approvals	cCSA _{US} , CE, CSA Star, CSA Flame	cCSA _{US} , CE, CSA Star, CSA Flame	cCSA _{US} , CE, CSA Star, CSA Flame	cCSA _{US} , CE, CSA Star, CSA Flame	cCSA _{US} , CE, CSA Star, CSA Flame

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. USA and Canada models are certified by C.S.A International.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

Printed in the U.S.A. ©Copyright 2011 Alliance Laundry Systems LLC